



EW410 Box IPC

Compact design. Multi-connectivity.

EW410NF7	
Enclosure	Heavy alu extrusion chassis Alluminium heat-sink 1x power led 1x Status led Lockable power connector Wall/VESA/DIN Rail Mounting option
CPU fanless	Intel Celeron J3455E Quad Core, 2M Cache, 1.5GHz (2.3 GHz)
Chipset	SoC
Embedded GPU	HDMI: resolution up to 3840x2160 DP: resolution up to 4096 x 2160 VGA: resolution up to 1920 x 1200
RAM	DDR3L 8GB SO-DIMM
Front I/O	Ethernet: 1 x GbE (RJ45) Serial: 2 x RS232/485 (DB9) Display: 1 x VGA - 1 x DP/HDMI combo Buttons: 1xPower - 1xReset Wi-Fi Antenna 3 x Wi-Fi Antenna Holes
Rear I/O	Ethernet: 3 x Gbe LAN (RJ45) USB: 2 x 3.0 Serial: 2 x RS232/RS422/RS485 (DB9)
Drives options	SATA: SSD 128GB, 256GB, 512GB, 1TB HDD 500GB, 1TB
Operating system	W10 IoT 64bit LTSC 2019 Linux support
Operating temperature (°C)	-20 +60
Storage temperature (°C)	-40..+85
Humidity	< 95% (non condensing)
Weight (kg)	0,7
Power supply	9 ~ 36 VDC
Dimensions (WxHxD)	180mm x 33mm x 121,2mm
Protection degree	IP30
Certifications	CE / EN 61000-6-2 / EN 61000-6-4 , FCC class A